

**AMENDMENTS TO THE CLAIMS**

The following listing of claims replaces all prior versions of claims in the application.

1. (Original): An optical element comprising:  
a polarizing element (A), separating incident light into polarization to then emit light, and made of a cholesteric liquid crystal, and  
a linearly polarized light reflection polarizer (B) transmitting linearly polarized light with one polarization axis and selectively reflecting linearly polarized light with the other polarization axis perpendicular to the one polarization axis, wherein  
the polarizing element (A) has a distortion rate with respect to emitting light to incident light in the normal direction of 0.5 or more and  
a distortion rate with respect to emitting light to incident light at an angle inclined from the normal direction by 60 degrees or more of 0.2 or less,  
the polarizing element (A) has a function increasing a linearly polarized light component of emitting light as incidence angle is larger.
2. (Original): The optical element according to claim 1, wherein, in the polarizing element (A), the linearly polarized light component of emitting light increasing as incidence angle is larger has a polarization axis of linearly polarized light substantially perpendicular to the normal direction of a surface of the polarizing element.
3. (Original): The optical element according to claim 1, wherein, in the polarizing element (A), the linearly polarized light component of emitting light increasing as incidence angle is larger has a polarization axis of linearly polarized light substantially parallel to the normal direction of a surface of the polarizing element.

4. (Currently amended): The optical element according to ~~any one of claims 1 to 3~~ claim 1, wherein the polarizing element (A) substantially reflects a non-transmission component of incident light.

5. (Currently amended): The optical element according to ~~any one of claims 1 to 4~~ claim 1, wherein a thickness of the polarizing element (A) is 2  $\mu\text{m}$  or more.

6. (Currently amended): The optical element according to ~~any one of claims 1 to 5~~ claim 1, wherein a reflection band width of the polarizing element (A) is 200 nm or more.

7. (Currently amended): The optical element according to ~~any one of claims 1 to 6~~ claim 1, wherein the linearly polarized light reflection polarizer (B) is a grid type polarizer.

8. (Currently amended): The optical element according to ~~any one of claims 1 to 6~~ claim 1, wherein the linearly polarized light reflection polarizer (B) is a multilayer thin film laminate with two or more layers made of two or more kinds of materials having a difference between refractive indices.

9. (Original): The optical element according to claim 8, wherein the thin multilayer laminate is a vapor-deposited thin film.

10. (Currently amended): The optical element according to ~~any one of claims 1 to 6~~ claim 1, wherein the linearly polarized light reflection polarizer (B) is a multi-birefringence layer thin film laminate with two or more layers made of two or more kinds of materials each having a birefringence.

11. (Original): The optical element according to claim 10, wherein the thin multilayer laminate is a stretched resin laminate with two or more layers containing two or more kinds of resins each having a birefringence.

12. (Currently amended): An optical element comprising a  $1/2$  wavelength plate (C) sandwiched between the polarizing element (A) and the linearly polarized light reflection polarizer (B) in the optical element according to ~~any one of claims 1 to 11~~ claim 1.

13. (Original): The optical element according to claim 12, wherein the  $1/2$  wavelength plate (C) is a broad band wavelength plate working as an almost  $1/2$  wavelength plate over the entire visible light band.

14. (Original): The optical element according to claim 13, wherein the  $1/2$  wavelength plate (C) has a front retardation values, which is expressed by  $(n_x - n_y) \times d$ , in the range of a  $1/2$  wavelength  $\pm 10\%$  at wavelengths in the light source wavelength band (ranging from 420 to 650 nm),

where a direction in which an in-plane refractive index is maximized is defined as X axis and a direction perpendicular to the X axis is defined as Y axis, where refractive indices in each axis directions are defined as  $n_x$  and  $n_y$ , respectively, and a thickness is defined as  $d$  (nm).

15. (Currently amended): The optical element according to ~~any one of claims 12 to 14~~ claim 12, wherein the  $1/2$  wavelength plate (C) controls a retardation in the thickness direction and reduces a change in retardation caused by a change in angle.

16. (Original): The optical element according to claim 15, wherein the  $1/2$  wavelength plate (C) has an  $N_z$  coefficient, which is expressed by  $N_z = (n_x - n_z)/(n_x - n_y)$ , in a relation of  $-2.5 < N_z \leq 1$ ,

where a direction in which an in-plane refractive index is maximized is defined as X axis, a direction perpendicular to the X axis is defined as Y axis and a thickness direction of the film is defined as Z axis, where refractive indices in each axis directions are defined as  $n_x$ ,  $n_y$  and  $n_z$ .

17. (Currently amended): The optical element according to ~~any one of claims 1 to 16~~ claim 1, wherein a polarizing plate is disposed outside of the linearly polarized light reflection polarizer (B) so that the polarized light transmission axis of the linearly polarized light reflection polarizer (B) and the polarization axis direction of the polarizing plate coincide with each other.

18. (Currently amended): The optical element according to ~~any one of claims 1 to 17~~ claim 1, wherein layers are laminated with a transparent adhesive or pressure sensitive adhesive.

19. (Currently amended): A light condensation backlight system, in which at least a light source is provided for the optical element according to ~~any one of claims 1 to 18~~ claim 1.

20. (Original): The light condensation backlight system according to claim 19, comprising a primary light condensing means condensing light in the angular range of  $\pm 60$  degrees from the normal direction.

21. (Original): The light condensation backlight system according to claim 20, wherein the primary light condensing means is a microprism sheet array disposed on the light source.

22. (Canceled)

23. (Canceled)

24. (New): A light condensation backlight system, in which at least a light source is provided for the optical element according to claim 12.

25. (New): The light condensation backlight system according to claim 24, comprising a primary light condensing means condensing light in the angular range of  $\pm 60$  degrees from the normal direction.

26. (New): The light condensation backlight system according to claim 25, wherein the primary light condensing means is a microprism sheet array disposed on the light source.

27. (New): A light condensation backlight system, in which at least a light source is provided for the optical element according to claim 17.

28. (New): The light condensation backlight system according to claim 27, comprising a primary light condensing means condensing light in the angular range of  $\pm 60$  degrees from the normal direction.

29. (New): The light condensation backlight system according to claim 28, wherein the primary light condensing means is a microprism sheet array disposed on the light source.

30. (New): A liquid crystal display, in which at least a liquid crystal cell is provided for the light condensation backlight system according to claim 28.

31. (New): The liquid crystal display according to claim 30, comprising a diffusing plate neither backscattering nor depolarizing laminated on the viewing side of the liquid crystal cell.